DF410 SCALPING UNIT *(EURO-TAIL)* Rev-9.2

On 300mm Extentions



HOPPER	
Width	1.9m (6'3")
Length	3.55m (11'8")
Max volume	4.5m³ (5.9yd ³)

SCREENBOX	
Top Deck	10' x 4' (3m x 1.2m)
Bottom Deck	10' x 4' (3m x 1.2m)
Angle	15° fixed

FEEDER BELT	
Width	1050mm (42")
Type	Plain Belt only
Control	Variable speed

FINES BELT	
Width	650mm (26")
Discharge Height	3.1m (10'1")
Control	Variable speed

MIDS BELT	
Width	650mm (26")
Discharge Height	2.8m (9'1")
Control	Variable speed

OVERSIZE BELT	
Width	900mm (36")
Discharge Height	3.1m (10'1")
Control	Variable speed

COLLECTION BELT	
Width	1050mm (42")
Control	Constant

TRACKS	
Width	300mm
Speed	1km/h

POWERPACK	
Diesel tank	260L (57 gallon/68 US gallon)
Hydraulic tank	375L (82 gallon/99 US gallon)

OPTIONS

1. Top deck: Finger tines, bofor bar
   punch plate or mesh
2. Radio remote control
3. Tier 3 - T.Deutz 2011 - 49Kw or JCB444 DieselMAX - 63Kw - ROW
   Tier 4i/Stage 3b - JCB EcoMAX 68Kw - EU (Until Dec 2019)
   Tier 4F - JCB444 EcoMAX - 55Kw - USA
   Stage V - T.Deutz 2.9L4 - 50Kw - EU

PERFORMANCE	
Max feed size	400mm
Capacity	up to 250 tph

WORKING DIMENSIONS	
Length	11.54M (37'7")
Width	11.25M (36'9")
Height	3.70M (12'1")

TRANSPORT DIMENSIONS	
Length	9.90M (32'5")
Width	2.35M (7'7")
Height	3.10M (10'1")

GENERAL			
Weight	15,600 kg	17.2 US TON	34400 lbs

ANACONDA® International

Copyright 2014 by Anaconda Equipment International. All rights reserved
This document or any part thereof must not be reproduced without the permission of Anaconda