

HOPPER

Width	1.38m (4' 5")
Length	2.8m (9' 1")

Max volume <i>(with tipping grid)</i>	5.8m ³ (7.1yd ³)
--	---

TIPPING GRID

Width	2.15m (7' 0")
Length	3.64m (11' 9")
Tip function	Radio remote or manual

SCREENBOX

Top Deck	10' x 4' (3m x 1.2m)
Bottom Deck	10' x 4' (3m x 1.2m)
Angle	28-36°

FEEDER BELT

Width	800mm (32")
Type	Plain belt
Control	Variable speed

MAIN BELT

Width	800mm (32")
Control	Variable speed

FINES (TAIL) BELT

Width	1050mm (42")
Discharge Height	2.85m (9' 1")
Control	Variable speed

MIDS BELT

Width	650mm (26")
Discharge Height	3.0m (9' 9")
Control	Variable speed

OVERSIZE BELT

Width	650mm (26")
Discharge Height	3.0m (9' 9")
Control	Variable speed

TRACKS

Width	300mm
Speed	1km/h

POWERPACK

Diesel tank	320L (70 gallon/84 US gallon)
Hydraulic tank	375L (82 gallon/99 US gallon)



OPTIONS

1. Screen decks: Mesh or piano wire
2. Radio remote control
3. Tier 3 - T.Deutz 2011 - 49Kw or JCB444 DieselMAX - 63Kw - ROW
 Tier 4i/Stage 3b - JCB EcoMAX 68Kw - EU (Until Dec 2019)
 Tier 4F - JCB444 EcoMAX - 55Kw - USA
 Stage V - T.Deutz 2.9L4 - 50Kw - EU

PERFORMANCE

Max feed size	75mm
Capacity	up to 200 tph

WORKING DIMENSIONS

Length	13.60M (44' 6")
Width	11.0M (36' 1")
Height	4.30M (14' 1")

TRANSPORT DIMENSIONS

Length	11.80M (39' 7")
Width	2.60M (8' 6")
Height	2.56M (8' 5")

GENERAL

Weight	15,500 kg	17 US TON	34000 lbs
--------	-----------	-----------	-----------



*Copyright 2014 by Anaconda Equipment International. All rights reserved
 This document or any part thereof must not be reproduced without the permission of Anaconda*